

**PRIORITY
DOCUMENT**
SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)

IB00/00826

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

REC'D 04 SEP 2000

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.


In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed

Dated 17th August, 2000.



This Page Blank (uspto)

9913193.0


Office

08 JUN 99 E452749-1 D02716
P01/7700 0:00 - 9913193.0

- 7 JUN 1999

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)



The Patent Office

Cardiff Road
Newport
Gwent NP9 1RH

1. Your reference

PAT 99312 GB

2. Patent application number

(The Patent Office will fill in this part)

3. Full name, address and postcode of the or of each applicant (underline all surnames)

NOKIA MOBILE PHONES LIMITED
KEILALAHDENTIE 4
02150 ESPOO
FINLAND

Patents ADP number (if you know it)

If the applicant is a corporate body, give the country/state of its incorporation

FINLAND 05911995004

4. Title of the invention

A CELLULAR COMMUNICATION TERMINAL
FOR ACCESSING SERVERS

5. Name of your agent (if you have one)

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

NOKIA IPR DEPARTMENT
NOKIA HOUSE
SUMMIT AVENUE
FARNBOROUGH
HAMPSHIRE
GU14ONG UK

Patents ADP number (if you know it)

07577633001

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number
(if you know it)

Date of filing
(day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
(day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:

- a) any applicant named in part 3 is not an inventor, or
 - b) there is an inventor who is not named as an applicant, or
 - c) any named applicant is a corporate body.
- See note (d))

YES

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

Description	16
Claim(s)	5
Abstract	1
Drawing(s)	7 <i>df</i>

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (*Patents Form 7/77*)

Request for preliminary examination and search (*Patents Form 9/77*)

1

Request for substantive examination (*Patents Form 10/77*)

Any other documents
(please specify)

11. I/We request the grant of a patent on the basis of this application.

Signature

Date

PAUL HIGGIN

7th June 1999

12. Name and daytime telephone number of person to contact in the United Kingdom

Miss K Jeffery 01252 865306

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.*
- Write your answers in capital letters using black ink or you may type them.*
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.*
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.*
- Once you have filled in the form you must remember to sign and date it.*
- For details of the fee and ways to pay please contact the Patent Office.*

PAT 99312 GBA cellular communication terminal, a method and a system for accessing servers.

- 5 The invention relates to a cellular terminal, method and a system for accessing different servers from a cellular terminal.

The Wireless Application Protocol (WAP) is a result of continuous work to define an industry wide standard for developing applications over cellular communication
10 networks. This makes it possible to access for example the Internet or other kind of information networks provided with hypermedia servers, from an ordinary cellular phone supporting WAP. These types of cellular phones which supports WAP, have only a small fraction of the resources of a typical desktop or portable computer. This means that the features in the phone are very limited compared to
15 a computer. The reason for this limitation is the size of the phones, i.e. the phone has a severe limitation in processing power, memory space, display size and buttons or keys by which a user can request, view and manipulate information obtained from a hypermedia server. Therefore, it is very important that the features in the phone are made as efficient as possible. Also, the relatively high
20 cost for a call from a cellular phone makes it also very important to provide the client with a fast response from the server.

The WAP Architecture is very similar to the Internet Architecture. Fig.1 shows a comparison between the Internet Architecture 10 and the WAP Architecture 20.
25 The Internet Architecture 10 comprises a Hypertext Markup Language (HTML) 12, e.g. Java Script, a Hypertext Transfer Protocol (HTTP) 14, Transport Layered Security (TLS) / Secure Sockets Layer (SSL) 16, and a Transport Configuration Protocol (TCP) / User Datagram Protocol (UDP) 18. The Internet Architecture 10 is well known prior art, and is disclosed in e.g. in US-A-5,657,390. The WAP
30 Architecture 20 comprises a Wireless Application Protocol (WAE) 22 corresponding to HTML 12, a Wireless Session Layer (WSP) 24 corresponding to HTTP 14, a Wireless Transport Layered Security (WTLS) 26 corresponding to TLS / SSL 16, and a Wireless Transport Layer (WTP) 28 corresponding to TCP / UDP 18. Furthermore, the WAP Architecture comprises different bearers 29 like e.g.

SMS, USSD and CDMA 30. There is also a possibility to implement different kinds of services and applications in the WAP Architecture, e.g. Value Added Services (VAS). The WAP Architecture 20 is well known prior art and is therefore not being disclosed any further. More detailed information about WAP can at present be found at the following Internet address: <http://www.wapforum.org/>

When using a WAP browser today, the session is normally between a dedicated gateway, connected to a server, and a client like a cellular phone. A gateway can be a computer that lies at the intersection of a server to be accessed and a client, and routes traffic from one or several servers to the client. Thus, the gateway provides a link between two disparate types of electronic communications such as the WAP architecture and the Internet architecture. If the user would like to access a remote server, i.e. a server which is located elsewhere than the server connected to the dedicated gateway, the access can in some way be restricted, or in some cases not allowed. For example, a user would like to receive information about his/her flight points from an airline company, which can be accessed through another gateway than the dedicated gateway. In this case, the browser in the phone will normally first establish a connection to the dedicated gateway. Then, the dedicated gateway will detect that the request is to another gateway than the dedicated gateway. This means that the browser application should initiate a linking application, e.g. a gateway application, in order to establish a session to the other gateway. The user must today confirm this request to initiate the session to the other server, and provide the browser with input of the location of the other gateway. Now, the phone can first establish a connection to the dedicated gateway, which in turn will cause the gateway to send a pull/push to the other gateway for the requested homepage, comprising the user's flight points. However, this means that the user must be provided with many different linking applications, e.g. one for each gateway, which accordingly takes up valuable memory space in the already limited space in a cellular phone.

Also, when browsing to an address on a network server, which is situated elsewhere than the dedicated gateway, the user should confirm this entry and register this on his/her radio terminal every time a session is going to be established to the other server. This confirmation/registration procedure is

intended to be some kind of alert to the user when he/she is switching from one gateway to another, but this will cause a delay in the response and requires that the user confirms this as well. Therefore, there is a need to make a faster and simplified connection to the WAP server which provides the requested information to the user.

An object of the invention is to provide a faster response to a user of a cellular telecommunication terminal supporting browsing facilities, like a cellular phone, which allow the user to be free from or at least minimise interaction, when accessing servers that is accessed through other linking means than the dedicated linking means. The linking means can be a gateway and/or a proxy, which provides a link between two disparate types of electronic communications such as WAP architecture and Internet architecture. It is also possible that the server itself physically comprises the linking means.

The basic idea of the invention is to enable the user to navigate among different linking means, which makes it possible for the user to choose between more or less faster servers.

This object is solved by providing a browser application which is arranged dynamically. This means that if the user would like to access linking means, which is not dedicated as a first linking means, the browser application will automatically activate a transmitter in the terminal to send a request to the first linking means to establish a session to the other linking means. Then the user will be free from interaction when accessing other servers that is accessed through other linking means than the first linking means.

A particular advantageous embodiment, is to provide the terminal with a script, which will provide provisions for accessing servers through linking means. This means that it can be possible to save valuable memory space in the terminal, since the terminal does not have to be provided with the different provisions which is required to access different linking means, like a gateway or a proxy. A provision can be a linking application, which a certain gateway requires to establish a session. Then the browser can, by means of the script, pull a linking

application from a gateway, and activate the linking application, after the application is pushed to the terminal. The pull and push process in this case could be a downloading process activated by the terminal. Thus, the application would be much more flexible and could easily be redefined, without the user having to be
5 worried about changes or updates in the application.

The invention will be described in greater detail in the following by way of example only and with reference to the attached drawings, in which

10 Fig. 1 shows a comparison between the Internet Architecture and the WAP Architecture;

Fig.2 schematically illustrates a preferred embodiment of a hand portable phone according to the present invention,

15

Fig. 3 schematically shows the essential parts of a telephone for communicating with a cellular or cordless network,

Fig. 4 schematically shows a connection between a communication
20 terminal and different linking means according to a preferred embodiment according to the present invention, and

Fig. 5 shows a flowchart over a method for accessing servers from a cellular telecommunication terminal, according to the present
25 invention.

Fig. 6a-c shows an example of a user interface in a phone according to the present invention.

30 Fig. 2 shows a preferred embodiment of a cellular communication terminal, hereafter also referred to as a phone, according to the present invention. The phone, which is generally designated by 1, comprises a user interface having a keypad 2, a display 3, an on/off button 4, a speaker 5, and a microphone 6. The phone 1 according to the preferred embodiment is adapted for communication via

a cellular telecommunication network, e.g. a cellular network. However, the phone could also have been designed for a cordless network. The keypad 2 has a first group 7 of keys as alphanumeric keys, by means of which the user can enter a telephone number, write a text message (SMS), write a name (associated with the phone number), etc. Each of the twelve alphanumeric keys 7 is provided with a figure "0-9" or a sign "#" or "*", respectively. In alpha mode each key is associated with a number of letters and special signs used in text editing. The keypad 2 additionally comprises two soft keys 8, two call handling keys 9, and a navigation key 10.

The two soft keys 8 have a functionality corresponding to what is known from the phones Nokia 2110™, Nokia 8110™ and Nokia 3810™. The functionality of the soft key depends on the state of the phone and the navigation in the menu by using a navigation key. The present functionality of the soft keys 8 is shown in separate fields in the display 3 just above the keys 8.

The two call handling keys 9 according to the preferred embodiment are used for establishing a call or a conference call, terminating a call or rejecting an incoming call.

The navigation key 10 is an up/down key and is placed centrally on the front surface of the phone between the display 3 and the group of alphanumeric keys 7. Hereby the user will be able to control this key by simply pressing the up/down key using his/her thumb, i.e. it allows the user to scroll between a group of items in e.g. a menu provided in the user interface. Since many experienced phone users are used to one-hand control, it is a very good solution to place an input key, requiring precise motor movements. Thus, the user may place the phone in the hand between the finger tips and the palm of the hand. Hereby, the thumb is free for inputting information. In another embodiment, the scroll key can be a roller key (not shown), which is arranged to rotate in one or several directions. The roller allows the user to roll the key to scroll between different items in a menu. In case of a roller key, the soft key 8 could be arranged to the roller, i.e. upon pressing on the roller the same functionality, as the operation key has, could be entered. The

roller key has a functionality corresponding to what is known from e.g. the phone Nokia 7110™, which also supports the Wireless Application Protocol (WAP). The roller key is incorporated by reference in US patent application 08/923,696.

5 Fig. 3 schematically shows the most essential parts of a preferred embodiment of the phone. These parts being essential to understand the invention. The preferred embodiment of the phone of the invention is adapted for use in connection with a GSM network, but, of course, the invention may also be applied in connection with other phone networks, such as other kinds of cellular networks and various forms
10 of cordless phone systems or in dual band phones accessing sets of these systems/networks. The microphone 6 records the user's speech, and the analogue signals formed thereby are A/D converted in an A/D converter (not shown) before the speech is encoded in an audio part 14. The encoded speech signal is transferred to control means 18. The control means 18 comprises a processor,
15 which may support software in the phone. The control means 18 also forms the interface to the peripheral units of the apparatus, wherein the peripheral units can comprise a RAM memory 17a and a Flash ROM memory 17b, a SIM card 16, the display 3 and the keypad 2 (as well as data, power supply, etc.). The control means 18 communicates with a transmitter/receiver means 19, e.g. a circuit which
20 is adapted to send/receive a request/respond to/from a telecommunication network. The audio part 14 speech-decodes the signal, which is transferred from the control means 18 to the earpiece 5 via a D/A converter (not shown).

The control means 18 is connected to the user interface. Thus, it is the control
25 means 18 which monitors the activity in the phone and controls the display 3 in response thereto. Therefore, it is the control means 18 which detects the occurrence of a state change event and changes the state of the phone and thus the display text. A state change event may be caused by the user when he activates the keypad including the navigation key 10, and these type of events are
30 called entry events or user events. However, the network communicating with the phone may also cause a state change event. This type of event and other events beyond the user's control are called non user events. Non user events comprise

status change during call set-up, change in battery voltage, change in antenna conditions, message on reception of SMS, etc.

Accessing servers from a cellular communication terminal.

5

Figure 4 schematically shows a system 301, comprising a cellular communication terminal 300, a cellular network 310, and a plurality of web servers 320 and 340 in an Internet network 350. The Internet network 350 uses World Wide Web (WWW) protocols. The cellular network 310 is arranged to establish a wireless connection
10 305 between a plurality of cellular terminals 300 and linking means 360. Even if the gateway is usually connected to a server to be accessed, it is possible that the gateway may be integrated together with the server to be accessed, as well.

The terminals 300 is able to access a web server 320 via the linking means 360.
15 In general, the linking means 360 is arranged to enable a session for the cellular communication terminal 300 and to forward data packets between the terminal and the web server 320. Thus, the web server 320 is arranged to receive and/or transmit data packets from/to the terminal 300. The transfer of data packets is often mentioned as pull and/or push. A pull could be described as the terminal
20 using the access point to access a location where the provider information is stored, and might also determine whether it has been updated and to retrieve it if necessary. In some cases it could also be possible to use a push, which could be described as the opposite to pull, i.e. the server maintains address data necessary to transfer updated information to the terminal.

25

The linking means 360 in this example is typically a gateway or a proxy, but is hereafter referred to as gateway. A proxy server is a process that allows the user to fetch different types of documents, like WWW, FTP, and GOPHER document. The proxy server can store the documents in a cache memory in the radio
30 terminal. What this means is that when anyone retrieves a document, besides transferring these files to the radio terminal, a copy is also made on the local host. Thus, the next time the user accesses that document, a request is sent to the remote host to see if the page has been updated, and if not, it is read directly from the cache memory. A gateway can be a computer that lies at the intersection of a

server to be accessed and a client, and routes traffic from one or several servers to the client. Thus, the function of the gateway is to provide a link between two disparate types of electronic communications such as WAP architecture and Internet architecture.

5

WAP defines a set of standard protocols that enable communication between mobile terminals and network servers. WAP uses a standard naming model according to which standard Internet URLs are used to identify content on origin servers. It also uses content typing. All WAP content is given a specific type consistent with WWW typing which allows a cellular terminal to correctly process the content based on type. WAP also uses standard content formats and standard communication protocols.

10

In this embodiment, the gateway 360 translates requests from a WAP protocol stack used by the cellular terminal 300 to a WWW (World Wide Web) protocol stack used by the web server. The web server can for example return WAP content such as WML (Wireless Markup Language) or WWW content such as HTML (HyperText Markup Language). In the later case a filter is used to translate the WWW content to WAP content e.g. HTML to WML. The gateway also encodes content sent over the cellular network to the cellular terminal and decodes data sent to it by the cellular terminal.

20

A Wireless Application Environment which forms an upper layer of the WAP stack includes a browser application, also called a microbrowser. The browser uses wireless markup language (WML) and a lightweight markup language, WMLScript a lightweight scripting language.

25

The terminals in this type of environment, are preferably cellular communication terminals, like cellular phones. Communication between a cellular terminal 300 and the gateway 360 is according to the Wireless Application Protocol (WAP). WAP specifies an application framework and network protocols for cellular terminals such as mobile telephones, pagers and personal digital assistants. WAP brings Internet content and advanced data services to cellular terminals. WAP can work across differing cellular network technologies and bearer types (GSM,

30

CDMA, SMS). Communication between the web server 320 and protocol gateway 360 is according to WWW protocols.

5 The cellular terminal differs from a desktop or a portable computer with Internet facilities in that generally it has a less powerful CPU, less memory, restricted power consumption, smaller displays and more limited input devices. The cellular network differs from the Internet network in that it generally has less bandwidth, more latency, less connection stability and less predictable availability. The WAP architecture is optimised for narrow bandwidth bearers with potentially high latency and is optimised for efficient use of device resources.

15 In order to communicate with the cellular network 310 and to receive and transmit data packets from at least one web server 320 through the gateway 360, the cellular communication terminal 300 comprises a receiver and a transmitter, see also Fig.3 ref. no. 19. The terminal 300 further comprises a first memory, see Fig.3 ref. no. 16 and 17b, provided with an identifier and at least one item. The item is provided with an access point which indicates the location of the server to be accessed, which could be indicated by means of a URL (Uniform Resource Locator) address. In addition, the item can also comprise data packets from earlier sessions which is updated upon a new session to the same access point. The identifier is used to identify the content at the address provided by the server, wherein the server is accessed by sending the identifier to the linking means to identify which type of content is requested at the server.

25 Also, an advantageous embodiment of the present invention is that the content in the item can comprise a script, which is arranged to provide provisions for accessing servers through linking means. The script can activate or download linking applications from a gateway, i.e. an application which makes it possible to receive and/or transmit different types of data packets between the server and the terminal. For example, the different types of data packets can be a particular text format, software programs, picture formats. This allows the processing power of the terminal to be restricted, allows a standard WAP browser to be used and provides flexibility for new features. This can be done by creating extensions to WML and WML script. Thus, the script can make it possible to access data

packets, which might not be supported by the software in the terminal, downloading the appropriate application, supporting the type of data format, directly to the terminal. In general, the data packets, can be data (content) stored or generated at an origin server 320. The content of the data packet is typically
5 displayed or interpreted by the client.

It is further possible to have one or more linking applications in the terminal from the beginning, i.e. to provide the linking application in the terminal before establishing a connection to a gateway. This is typically done in the manufacturing
10 process of the terminal, wherein the linking application can be a software program controlling the access to the server.

As mentioned before, the Wireless Application Environment forms an upper layer of the WAP stack, which includes a browser application. To access different
15 servers the terminal must be provided with a browser application, like a so called microbrowser. The browser application is arranged to establish a session to at least a first gateway by reading the item in the first memory. A user interface is connected to the browser application having a display for displaying content and user input means to control the browser. An example of how the user interface can
20 be displayed during a session is shown in Fig. 6a-c. The input means is shown in Fig. 2 as the keypad 2. The browser can be arranged in a ROM memory or on a SIM card, as shown in Fig. 3 ref. No. 17b and 16, respectively.

In an another preferred embodiment, the terminal can be provided with a second
25 memory, which is arranged to copy items from a session. Thus, the items from a session can be stored in this second memory. Typically, this second memory can be a cache memory, which means that the items from the latest session can be temporarily saved in the second memory. The cache memory could be identified as the RAM memory 17a in Fig. 3. As an alternative, it can also be possible to
30 save the items from a session in a permanent storage memory, which means that the user is able to confirm if the items are going to be saved or deleted. The permanent storage memory could be identified as the SIM card 16 and/or the ROM memory 17b as shown in Fig. 3.

In accordance with the present invention, the browser application is arranged dynamically. This means that, if the access point indicates a location to a second gateway 330, which gives access to the server 340, the browser application will automatically activate the transmitter to send a request to the first gateway 360 to access the server 340 through the second gateway 330. This request can comprise the URL address of the server, together with the identifier, identifying the content of the requested content, and that the user will accept to connect to another gateway, in order to reach this address. Thus, this will allow the user to be free from interaction when accessing other servers that is accessed through other linking means than the first linking means. Naturally, it can still be possible to enable an authorisation confirmed by the user, but this could slow down the user, when he/she is going to browse to a gateway which is not the first gateway. Of course, there might be some gateways which contains a certain risk, upon entering, but in such cases it can be possible for the user to set some security settings in the browser application, in order to minimise the risk of security hazards. An example illustrating how to send and receive data packets from the server is described in more detail with reference to Fig. 5.

The method for accessing servers through a cellular communication terminal.

Fig. 5 shows a flow chart, in accordance with the present invention, describing a way of accessing servers through a cellular communication terminal. The cellular telecommunication terminal in this example is the same type as described in Fig. 2 and 3, and the apparatus is hereafter also referred to as a phone. The phone is provided with a browser application and a first memory which enables the user to browse among different objects on a server. This browsing can be done by using a microbrowser supporting WAP. When the phone is activated and establishes, a wireless connection to a cellular network, e.g. when the phone roams to a new network, "START" 500, it is possible to communicate with different telecommunication services, e.g. WAP related services, i.e. a service which can be accessed from a server to the phone. By using this kind of service, it might be possible to obtain information from a server to the phone, e.g. by using SMS (Short Message Service), or a similar service.

First, the user may select a browser menu on a display controlled by the browser application, which is connected to the first memory. In this browser menu the user can choose to establish a session to a server. To establish the session the user selects the service connected to the server from the menu. The selection is done
5 by e.g. pressing on one of the softkeys as shown in Fig. 2. Then the browser application reads and identifies the content of an item from the first memory "READ ITEM" 510. This item comprises at least one access point, which indicates the location of the server to be accessed. The item might comprise more content than the access point, e.g. it is possible to have data packets from an earlier
10 session which is updated upon a new session to the same access point. The first memory is also provided with an identifier, which is used to identify the type of content at the server. After reading the item from the first memory, the browser application generates a request, "GENERATE REQUEST" 520. This request comprising information of the access point to be accessed, and the identifier
15 identifying the type of content at the server. The information could for example be a URL address, where the server is located.

The request is then forwarded to the linking means, "FORWARD REQUEST" 530, in order to establish a session between the linking means and the terminal. The
20 linking means could be a gateway or a proxy server, which links the requested information to the correct access point. If the linking means do not respond to the request, "RECEIVED REQUEST?" 540, e.g. because the linking means is broken or the terminal does not have coverage to the cellular network, the terminal could receive an error message, which says that a connection to the linking means could
25 not be established. Then, the user could choose to re-send the request once more, "FORWARD REQUEST" 530.

In an advantageous embodiment of the present invention, the content of the item can comprise a script, which is arranged to provide provisions for accessing
30 servers through the linking means. The script can activate or download linking applications from a gateway, i.e. an application which makes it possible to receive and/or transmit different types of data packets between the server and the terminal. For example, the different types of data packets can be a particular text format, software programs, different picture formats, etc. This allows a standard

WAP browser to be used and provides flexibility for new features. This can be done by creating extensions to WML and WML script. Thus, the script can make it possible to access data packets, which might not be supported by the software in the terminal, by downloading the appropriate application, supporting the type of data format, directly to the terminal. In general, the data packets, is data (content) stored or generated at an origin server. The content of the data packet is to be displayed or interpreted by the client.

It is further possible to have one or more linking applications in the terminal from the beginning, i.e. to provide the linking application in the terminal before establishing a connection to a gateway. This is typically done in the manufacturing process of the terminal, wherein the linking application can be a software program controlling the access to the server.

After the terminal has been connected to the linking means, the linking means can control that the access point is correct, "ACCESS POINT KNOWN?" 550. For example, if the user has requested access to a server which no longer exists, is misspelt, or for some other reason is no longer known, the linking means could transmit an error message. This error message could then be displayed on the terminal, "DISPLAY ERROR MESSAGE" 560, providing the user with information about the error. Then the session could be terminated, either by the user or the linking means, "END" 570. If the access point is known, the linking means can send a pull to the server, "SEND PULL TO THE SERVER" 580. A pull could be described as the terminal uses the access point to access a location where the provider information is stored, and might also determine whether it has been updated and to retrieve it if necessary. In some cases it could also be possible to use a push, which could be described as the opposite to pull, i.e. the server maintains address data necessary to transfer updated information to the terminal.

Finally, when the server has sent the requested information to the linking means, the information will be linked further from the linking means to the terminal, "DISPLAY CONTENT" 590.

In accordance with the present invention, the browser application is arranged dynamically, i.e. if the access point indicates a location to another linking means, which gives access to the server, the browser application will automatically activate a transmitter in the terminal to send a request to the first linking means to access the server through the second linking means. This request can comprise the URL address of the server, and that the user will accept to connect to the second linking means, in order to reach this address. Thus, this will allow the user to be free from interaction when accessing other servers that is accessed through other linking means than the first linking means. Naturally, it can still be possible to enable an authorisation confirmed by the user, when he/she is going to browse to another linking means which is not the first linking means.

The user interface.

With reference to Fig. 6a, 6b and 6c, an example is shown of how the display in a user interface can act when accessing a server according to the present invention. The user interface may comprise the same elements as shown in Fig.2, i.e. a keypad 2, a display 3, an on/off button 4, a speaker 5 and a microphone 6. Also, the terminal is provided with control means 18 as shown in Fig. 3, which controls the user interface. Starting from Fig. 6a, there is a layout 31 presented on a display in a phone, as shown in Fig.2 and 3, which indicates signal strength 35 from the cellular telecommunication network "D1 Telekom" 40, the battery power 45 and a clock showing the time 50 in hours and minutes. Preferably, the display in the phone is an LCD (Liquid Crystal Display) display. The display, can be controlled by the control means. The layout 30 presents an example of the phone in idle mode, i.e. when the phone is activated and awaiting an action, e.g. an incoming or outgoing call. In the bottom of the display there are two items which are denoted as "Menu" 55 and "Names" 60. If the user selects "Names" 60 he/she can e.g. access a built in phone book. If the user selects "Menu" 55, he/she can select among several different menus. The actual selection of features in the bottom of the display, like "Menu" and "Names", can be selected by means of the soft keys disclosed with reference to Fig. 2.

One of the menus can be the next layout 65 called "Browser" 70. If the user chooses to use this menu, he/she can access different telecom related information services, e.g. Internet. One way of accessing this kind of information is to use the Wireless Application Protocol, WAP.

5

If the user chooses to select "Home" 71, this may lead to the next layout 75, which graphically indicates, "Connecting to Service" 80. This shows an example of how the phone is trying to establish a connection to e.g. Internet, by sending an access request, through a first gateway, to a server. If a connection is established to the first gateway, some kind of welcome text for a home page might be displayed, "Welcome to D1 Web." 90. If the user selects "Options" 90 a list of selections can be displayed as shown in the following layout 110. For example, the different choices could be "Currency converter" 115, "White pages" 120, "Pizza" 125, "CNN" 130, etc. In this example the user selects to use the currency converter 115, and browses further to the server providing this service in the next layout 135. In this layout 135 a browser display is shown with the selected item, which is indicated as a link to a service which provides a currency conversion. The user can select to send a request for the chosen item, by using the "Options" 140.

This leads to the next layout 150, as shown in layout 75, which graphically indicates, "Connecting to Service" 155. This shows an example of how the phone is trying to establish a connection to e.g. the application (currency converter 115), by sending a request to the server. If a connection is established, some kind of information text for the currency converter might be displayed. The following reference numbers refers to Fig. 6b: 160-230. For example, the layout can be provided with different editable fields and selection list placeholders, which in this example are shown in square brackets ([]). The selection which is highlighted can indicate a default state of the selection. In these fields, the user can input an amount, "Amount:[]" 165, in one currency, "From:[DKK]" 170, converted into another currency, "converted to:[DKK]" 175. When the user is going to enter an amount 185, e.g. 200, on how much he/she would like to convert, the layout may e.g. change its outlook like it does in layout 180. Thereafter, the user may press Ok 190, whenever he/she is done, or clear the amount by selecting "Clear" 191.

The steps for choosing a first currency to convert from 170, and choosing a second currency to convert to 175, are repeated in the layouts 195-205. Thereafter, the user may select "Options" 210, in layout 205, which in this example
5 activates the calculation of the currency conversion and displays the result 220 in the next layout 215.

If the user would continue with his/hers currency conversion, and choose another currency to convert to, the user selects the option "converted to [DKK]:" 225, which
10 becomes highlighted upon selection, and is shown in layout 230. The following reference numbers refers to Fig. 6c: 235-270. In the next layout 235, a selection list of available currencies is displayed. The user selects e.g. *USD* 240, and selects the entry by selecting "Ok" 245. The next layout 250 highlights the selected currency USD 255 to convert to. Thereafter, the user may select "Options" 260,
15 which in this example once again activates the calculation of the currency conversion and the result "[USD]: 36,36" 265 is displayed with the selected information in the next layout 270.

If the currency conversion service is provided on a second gateway, instead of the
20 first gateway, the invention enables the first gateway to automatically forward the request to the second gateway. In this manner, this action can be invisible for the user, and free him/her from any user interaction.

The invention is not limited to the above described and in the drawing shown an
25 example of embodiments but can be varied within the scope of the appended claims. For example, a gateway and a proxy is normally working as a server, and could therefore be working as one unit, i.e. gateway/proxy is also working as a server.

CLAIMS

1. A cellular communication terminal (1,300) for accessing servers (320-360), said
5 terminal comprising
- a receiver and a transmitter (19) arranged to receive and transmit data packets from at least one server (320,340) through linking means (360) arranged to forward the data packets between the terminal (1,300) and the server (320,340);
 - 10 - a first memory (16,17b) comprising an identifier and at least one item, the item is provided with an access point which indicates the location of the server (320,340) to be accessed, wherein the server (320,340) is accessed by sending the identifier to the linking means (360) to identify the content to be accessed at the server (320,340);
 - 15 - a browser application, arranged to establish a session to at least a first linking means (360) by reading an item from the first memory (16,17b), and
 - a user interface (2,3,4,5,6) connected to the browser application having display means (3) for displaying content received from the server (320,340) and user input means (2,4,5) to control the browser application,
 - 20 characterized *in* that the browser application is arranged dynamically, such that if the access point indicates a location to a second linking means (330) giving access to the server (340), the browser application will automatically activate the transmitter (19) to send a request to the first linking means (360) to access said server (340) through second linking means (330), in order to allow the user to be
 - 25 free from interaction when accessing other servers that is accessed through other linking means than the first linking means.
2. A cellular communication terminal according to claim 1, characterized *in* that the
30 terminal (1,300) is provided with a second memory (17a) arranged to copy the item from a session.
3. A cellular communication terminal according to claim 2, characterized *in* that said second memory (17a) is a cache memory.

4. A cellular communication terminal according to any of the preceding claims characterized *in* that said first memory is a SIM card (16).

5. A cellular communication terminal according to any of the preceding claims, characterized in that said communication terminal is arranged to use a desktop computer or a portable computer as the first and/or second linking means (330,360).

6. A cellular communication terminal according to any of the preceding claims, characterized in that the item further comprises a script, which is arranged to provide provisions for accessing servers (320,340) through linking means (330,360).

7. A cellular communication terminal according to claim 6, characterized in that said script is arranged to activate a linking application.

8. A cellular communication terminal according to any of the preceding claims, characterized in that said terminal is arranged with a linking application, to control the access to different servers.

9. A method for accessing servers through a cellular communication terminal (1,300), said communication terminal comprising a first memory (16,17b) and a browser application, wherein the method comprises the following steps:

- reading an item (510) in said first memory (16,17b) and an identifier, by means of said browser application, said item comprising at least one access point indicating the location of a server (320,340) to be accessed;
- generating a request (520) by means of said browser application, said request comprising information of the requested access point, and the identifier identifies the content of the requested access point,
- initiating a session to a first linking means (360), by forwarding the request from the communication terminal (1,300) to the first linking means (360), said linking means send data packets between the terminal (1,300) and the server (320,340),
- identifying the request (550) at the first linking means (360), and

- establishing a session between said terminal (1,300) and said first linking means (360) by sending a response from the first linking means to the terminal,

characterized in that the browser application is dynamic, such that if the access point is indicating a location to a second linking means (330) giving access to said server (340), the browser application is automatically activating a transmitter (19) by sending a request to the first linking means (360), forwarding the request to said second linking means (330) and providing access (580) to the server (340), in order to allow the user to be free from interaction when accessing other servers that is accessed through other linking means than the first linking means.

10. A method according to claim 9, characterized in that the item in the session are copied and stored in a second memory (17a).

11. A method according to claim 9 or 10, characterized in that said communication terminal is using a desktop computer or a portable computer as the first and/or the second linking means (330,360).

12. A method according to claim 9, 10 or 11, characterized in that the item further comprises a script, which provides provisions for accessing servers (320, 340) through linking means (330,360).

13. A method according to claim 12, *characterized in* that said script is activating a linking application.

14. A method according to claim 9, 10, 11, 12 or 13, characterized in that said terminal is provided with a linking application, controlling the access to different servers.

15. A system (301) for accessing servers (320-360), said system (301) comprising

- a cellular communication terminal (1,300) having:
 - a receiver and a transmitter (19) arranged to receive and transmit data packets from at least one server (320,340) through linking means (360)

arranged to forward the data packets between the terminal (1,300) and the server (320,340);

- a first memory (16,17b) comprising an identifier and at least one item, the item is provided with an access point which indicates the location of the server (320,340) to be accessed, wherein the server (320,340) is accessed by sending the access point and the identifier to the linking means (360) to identify the content to be accessed;
- a browser application, arranged to establish a session to at least a first linking means (360) by reading an item from the first memory (16,17b), and
- a user interface (2,3,4,5,6) connected to the browser application, having display means (3) for displaying content and user input means (2,4,6) to control the browser application,
- a cellular communication network (310), arranged to establish a connection (305) between the cellular communication terminal (1,300) and linking means (360),
- at least one first linking means (360), arranged to enable a session for said cellular communication terminal (1,300) and to forward data packets between the terminal and a server (320,340), and
- at least one server (320,340), arranged to receive and/or transmit data packets from/to the terminal (1,300),

characterized in that the browser application is arranged dynamically, such that if the access point indicates a location to second linking means (330) giving access to the server (340), the browser application will automatically activate the transmitter (19) to send a request to the first linking means (360) to access said server (340) through second linking means (330), in order to allow the user to be free from interaction when accessing other servers that is accessed through other linking means than the first linking means.

16. A system according to claim 15, characterized in that the terminal (1,300) is provided with a second memory (17a) arranged to copy the item from a session.

17. A system according to claim 16, characterized in that said second memory (17a) is a cache memory.

18. A system according to claim 15, 16 or 17, characterized in that said first memory is a SIM card (16).

19. A system according to claim 15, 16, 17 or 18, characterized in that said communication terminal is arranged to use a desktop computer or a portable computer as the first and/or the second linking means (330,350).

20. A system according to claim 15, 16, 17, 18 or 19, characterized in that the item further comprises a script, which is arranged to provide provisions for accessing servers (320,340) through linking means (330,360).

21. A system according to claim 20, characterized in that said script is arranged to activate a linking application.

22. A system according to any one of the claims 15-21, characterized in that said terminal is arranged with a linking application, to control the access to different servers.


22. A system according to any one of the claims 15-22, characterized in that communication between the server and the terminal is in accordance with the Wireless Application Protocol.

Abstract

A system (301), a method, and a cellular communication terminal (1,300) for
accessing servers (320-360). The cellular communication terminal (1,300) is
5 arranged with a receiver and a transmitter (19), to receive and transmit data
packets from at least one server (320,340) through linking means (360). The
linking means is arranged to forward the data packets between the terminal
(1,300) and the server (320,340). The terminal is further arranged with a first
memory (16,17b) comprising an identifier and at least one item. The item is
10 provided with an access point, which indicates the location of the server (320,340)
to be accessed. The server (320,340) is accessed by sending the access point
and the identifier to the linking means (360) to identify the content to be accessed.
A browser application is arranged in the terminal, to establish a session to at least
a first linking means (360), by reading an item from the first memory (16,17b).
15 Also, the terminal has a user interface (2,3,4,5,6) connected to the browser
application. The user interface comprises display means (3) for displaying content
and user input means (2,4,6) to control the browser application.

20 (Fig. 4)

Fig.1



This Page Blank (uspto)




Fig. 2





Fig. 3


This Page Blank (uspto)

Fig.4



This Page Blank (uspto)

Fig. 5



This Page Blank (uspto)




FIG 6a

This Page Blank (uspto)





Fig 6 b

This Page Blank (uspto)



*** THE END ***

FIG 6c

This Page Blank (uspto)